

## Technical Data Sheet

### General Description

We revolutionized drywall installation by providing the world's first fiberglass drywall joint tape - a stronger alternative to paper. ToolPro self-adhesive fiberglass mesh is thin and light, but extremely strong and easy to use, and greatly increases joint strength and durability for less cracking.

### Technical Characteristics

Property	Imperial	Metric	ASTM Method
MD Yarn:	150 1/0 Fiberglass	330 Dtex Fiberglass	N/A
CD Yarn:	75 1/0 Fiberglass	680 Dtex Fiberglass	N/A
Stitch Yarn:	40 Denier Polyester	44 Dtex Polyester	N/A
Warp Construction:	9 yarns/inch	3.6 yarns/cm	D-3775
Weft Construction:	8 yarns/inch	3.2 yarns/cm	D-3775
Warp Tensile:	50 lbs/in	437 N/5cm	C-474
Weft Tensile:	50 lbs/in	1,094 N/5cm	C-474
Thickness:	0.011 in	279.4 microns	D-1777 & C-475
Weight:	1.643 oz/yd <sup>2</sup>	55.71 g/m <sup>2</sup>	D-3776
Coating:	SBR Latex		
Adhesive:	Pressure Sensitive Adhesive		
Construction Type:	Weft Knit Insertion		

All statements herein are expressions of opinion, which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our product are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind, expressed or implied, is made or intended. Values presented above are nominal and only to be used as guidelines.



### Properties

- Requires no embedding coat, which also reduces drying time.
- Open fiberglass mesh eliminates blisters and bubbles.
- Self-adhesive for easy application.

