

**CP 27® 14-DAY SHURRELEASE® BLUE PAINTER'S TAPE - MULTI-SURFACE****TYPICAL APPLICATIONS**

- For interior and exterior use on multiple surfaces, including painted walls, glass, vinyl, metal and wood
- Not recommended for use on wallpaper, unpainted wallboard, ceiling tile or with uncured coatings

**PRODUCT FEATURES**

- Premium grade, multi-surface ShurRELEASE® blue painter's tape
- Medium adhesion
- UV-resistant
- Easy, no-residue removal
- Prevents lifting and paint seepage for cleaner paint lines
- Solvent-free, high performance adhesive bonds quickly to the surface, allowing for painting immediately after application
- Great for temporary indoor floor marking and removes cleanly from most surfaces for up to 60 days. Not recommended for hardwood floors
- \*Test before use on all surfaces and when using solvent-based coatings

**CONSTRUCTION**

Backing: Fine structured crepe

Adhesive: Synthetic rubber-based adhesive

**STANDARD WIDTHS**

0.7 in; 0.94 in; 1.41 in; 1.88 in

18 mm; 24 mm; 36 mm; 48 mm

**STANDARD LENGTH**

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

**STANDARD CORE SIZE**

3 in

**APPLICABLE STANDARDS**

NA

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

**COLOR****PHYSICAL PROPERTIES**

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

**STANDARD**

32.5 oz/in width

10%

50 F to 200 F

22.5 lbs/in width

5.08 mils

**METRIC**

3.56 N/10 mm

10%

10 C to 93 C

39.4 N/10 mm

0.13 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

